

## 886 DATA NOT CONVERTED FROM SOURCE FORMAT

### Field Definition and Scope

Data for which there is no specific UNIMARC field.

It is used when an agency is converting records from another format and wishes to retain elements in fields which have no equivalent.

### Subfields & Occurrence

| Field/Subfield | Field/Subfield Name                                 | Repeatability | Occurrence |
|----------------|---|---------------|------------|
| 886            | DATA NOT CONVERTED FROM SOURCE FORMAT               | R             | O          |
| a              | Tag of the Source Format Field                      | NR            | O          |
| b              | Indicators and Subfields of the Source Format Field | NR            | O          |
| 2              | Source  | NR            | O          |

### Indicators

| Indicator | Value | Description   |
|-----------|-------|---|
| 1         |       | Specifies the Type of Field   |
|           | 0     | Record Label  |
|           | 1     | Variable control field (0-- fields without indicators or subfields) |
|           | 2     | Variable data field (010-999 fields)                                |
| 2         | #     | blank (not defined)   |

### Subfields Description

#### \$a Tag of the Source Format Field

This subfield will not be present if Indicator 1 has the value 0. Not repeatable. This subfield can be used only once with the value Tag of the Source Format Field. All other \$a subfields in this field have the values assigned by the field of the source format.

#### \$b Indicators and Subfields of the Source Format Field

This subfield will contain the indicators, subfield identifiers and subfields of the original field in their original order. Not repeatable. This subfield can be used only once with the value Indicators and Subfields of the Source Format Field. All other \$b subfields in this field have the values assigned by the field of the source format.

#### \$2 Source

The name of the format used for the machine-readable record. See UNIMARC/Bibliographic format, Appendix A codes. Not repeatable.

See also specification of [Control Subfield 2](#).

### Examples

|   |
|---|
| EX 1  |
| 886 2#\$2usmarc\$a042\$b##\$alc   |
| There is no equivalent in UNIMARC for USMARC's Authentication Code. There are only three true subfield identifiers in the field – the \$2, the first \$a and the first \$b. |

**History**

|      |  |
|------|--|
| 2001 | New field.   |
| 2009 | Updated definition/scope: \$a Tag of the source format field.                      |
| 2009 | Updated definition/scope: \$b Indicators and subfields of the source format field. |